

# PICK-UP BROOMS

BR60 | BP72 | BR72 | BP84 | BR84



JOHN DEERE



# Pick-Up Brooms

BR60 | BP72 | BR72 | BP84 | BR84



## Specifications

- Pick-up brooms feature a 635-mm (25 in.)-diameter brush with 50/50 poly wire brush segments and a baffle to hold debris in bucket.
- Heavy-duty, high-torque drive motor is coupled to the brush core through a 25.4-mm (1 in.) splined shaft.
- Bolt adjustment on brush provides infinite height control.
- Two standard caster wheels (not on fixed brooms) allow for better balance and stability when sweeping.
- During bristle replacement, the drive motor can be pulled from the brush core without disconnecting any hydraulic lines. This means less mess and cleanup, with little chance of hydraulic fluid contamination.
- Optional gutter brush has adjustable flow to allow for different material applications and the ability to turn off when not in use.
- Like all Worksite Pro™ attachments, these pick-up brooms are optimized to work with John Deere G- and E-Series Skid Steers and Compact Track Loaders (CTLs), and K-Series Compact Loaders. They're also compatible with many competitive models. See your local Deere skid steer dealer for details.

	BR60	BP72	BR72	BP84	BR84
<b>Brush Diameter</b>	635 mm (25 in.)	635 mm (25 in.)	635 mm (25 in.)	635 mm (25 in.)	635 mm (25 in.)
<b>Core Diameter</b>	162 mm (6.38 in.)	162 mm (6.38 in.)	162 mm (6.38 in.)	162 mm (6.38 in.)	162 mm (6.38 in.)
<b>Number of Wafers</b>	34	44	44	50	50
<b>Sweeping Width</b>	1524 mm (60 in.)	1828 mm (72 in.)	1828 mm (72 in.)	2133 mm (84 in.)	2133 mm (84 in.)
<b>With Gutter Brush</b>	1930 mm (76 in.)	2235 mm (88 in.)	2235 mm (88 in.)	2540 mm (100 in.)	2540 mm (100 in.)
<b>Working Width</b>	1905 mm (75 in.)	2184 mm (86 in.)	2187 mm (86.1 in.)	2489 mm (98 in.)	2492 mm (98.1 in.)
<b>Height</b>	736 mm (29 in.)	736 mm (29 in.)	736 mm (29 in.)	736 mm (29 in.)	736 mm (29 in.)
<b>Length</b>	1372 mm (54 in.)	1549 mm (61 in.)	1354 mm (53.3 in.)	1549 mm (61 in.)	1354 mm (53.3 in.)
<b>Operating Weight Without Gutter Brush</b>	340 kg (750 lb.)	681 kg (1,500 lb.)	431 kg (950 lb.)	772 kg (1,700 lb.)	476 kg (1,050 lb.)
<b>Hydraulic Flow</b>					
Minimum	45 L/min. (12 gpm)	37.8 L/min. (10 gpm)	37.8 L/min. (10 gpm)	37.8 L/min. (10 gpm)	37.8 L/min. (10 gpm)
Maximum	83 L/min. (22 gpm)	113.5 L/min. (30 gpm)	113.5 L/min. (30 gpm)	113.5 L/min. (30 gpm)	113.5 L/min. (30 gpm)
<b>Hopper Capacity</b>	0.37 m <sup>3</sup> (13.2 cu. ft.)	0.40 m <sup>3</sup> (14.3 cu. ft.)	0.45 m <sup>3</sup> (15.75 cu. ft.)	0.47 m <sup>3</sup> (16.7 cu. ft.)	0.52 m <sup>3</sup> (18.21 cu. ft.)
<b>Hopper Dumping</b>	With skid steer bucket cylinder	With skid steer bucket cylinder	With skid steer bucket cylinder	With skid steer bucket cylinder	With skid steer bucket cylinder
<b>Vehicle Compatibility</b>	312GR, 314G, 316GR, and 318G Skid Steers; and 317G Compact Track Loader	318G/E, 320E, 324E, 328E, and 332E Skid Steers; and 317G, 323E, 329E, and 333E CTLs	318G/E, 320E, 324E, 328E, and 332E Skid Steers; 317G, 323E, 329E, and 333E CTLs; and 204K and 304K Compact Loaders	318G/E, 320E, 324E, 328E, and 332E Skid Steers; and 317G, 323E, 329E, and 333E CTLs	318G/E, 320E, 324E, 328E, and 332E Skid Steers; 317G, 323E, 329E, and 333E CTLs; and 204K, 244K, 304K, and 324K Compact Loaders
<b>Options</b>	Gutter brush	Gutter brush	Gutter brush	Gutter brush	Gutter brush
<b>John Deere Standard Warranty</b>	One-year unlimited hours	One-year unlimited hours	One-year unlimited hours	One-year unlimited hours	One-year unlimited hours

**WORKSITE PRO™**

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

