

Augers

PA15 | PA30



JOHN DEERE



Augers

PA15 | PA30



Specifications

- Heavy-duty unit drives the auger through a planetary gear reduction. All moving components run in oil for constant lubrication. Spring-loaded double-lip seals guard against contamination.
- Reverse rotation allows quick back-out when obstructions are encountered. Also helps shed dirt from the auger when working in wet conditions.
- Choose from a variety of auger bit styles and diameters including standard 102–914 mm (4–6 inch), 220–305-mm (9–12 inch) rock and frost, and 457–914-mm (18–36 inch) tree and shrub.
- Like all Worksite Pro™ attachments, these augers are optimized to work with John Deere skid steers, compact track loaders, compact excavators, and the compact four-wheel-drive loader, and are compatible with most competitive models. Plus, they're backed by a one-year warranty and one-of-a-kind parts and service. See your local John Deere skid steer dealer for details.

	PA15	PA30
Maximum Auger Bit Diameter	610 mm (24 in.)	914 mm (36 in.)
Overall Auger Bit Length	1219 mm (48 in.)	1219 mm (48 in.)
Hydraulic Flow		
Minimum	23 L/min. (6 gpm)	53 L/min. (14 gpm)
Maximum	57 L/min. (15 gpm)	114 L/min. (30 gpm)
Maximum Continuous Operating psi	20 684 kPa (3,100 psi)	20 684 kPa (3,100 psi)
Output Shaft Options	51-mm (2 in.) Hex	51-mm (2 in.) Hex
Output Torque	1942 Nm (1,433 lb.-ft.)	3784 Nm (2,791 lb.-ft.)
Output Speed		
23 L/min. (6 gpm)	38 rpm	—
30 L/min. (8 gpm)	51 rpm	—
38 L/min. (10 gpm)	64 rpm	—
45 L/min. (12 gpm)	77 rpm	—
57 L/min. (15 gpm)	96 rpm	49 rpm
68 L/min. (18 gpm)	—	59 rpm
76 L/min. (20 gpm)	—	66 rpm
106 L/min. (28 gpm)	—	92 rpm
Vehicle Compatibility	313, 315 Skid Steers; CT315, 319D Compact Track Loaders; 17D, 27D Compact Excavators	318D, 320D, 326D, 328D, 332D Skid Steers; 319D, 323D, 329D, 333D Compact Track Loaders; 244J Compact Loader; 35D, 50D, 60D Compact Excavators

WORKSITE PRO™

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

