## DrizAir® 1200 The Classic Refrigerant Dehumidifier

## **Product Features**

- Removes up to 15 gallons a day
- Super convenient size
- Hot-gas bypass for fast defrost
- Rugged rotomolded housing stackable!
- Electronic touch-pad controls
- Rigid handle designed for rugged service
- Semi-pneumatic wheels for easy transport
- Built-in duct attachment ring
- If power is interrupted during operation, the unit will automatically restart when power is restored. (115V models only.)



Item #F203-A \$1,485 Suggested List *U.S. Funds* 

## **Product Specifications**

Troduct Spec	medelons		
Model	F203-A		
Туре	Standard refrigerant		
Dimensions H $\times$ W $\times$ D	$32 \times 20 \times 19.5$ in. $83 \times 50 \times 50$ cm		
Use weight	80 lbs.   36 kg		
Power	115V, 6.4 amps		
Water removal max. (at saturation)	145 pints   68.6 liters /day		
Water removal AHAM (80°F/60%RH)	64 pints   30 L/day		
Temperature operating range	33°-100°F   1°-38°C		
Compressor type	6670 BTU rotary		
Defrost type	Hot-gas bypass		
Process air output	227 CFM		
Controls	Electronic touchpad		
Water pump-out	Centrifugal		
Drain hose length	40 ft.   12 m		
Air filter	3M HAF (High Airflow)		
Wheels	Semi-pneumatic		
Handle	Rigid		
Stackable	Stack up to 2 high for storage		
Housing	Rotomolded polyethylene		
Safety	ETL listed to CSA 22.2 #92		