

FORCE/1

Insulation Blowing Machine



Exceptional Performance

Intec's FORCE/1 processes up to 970 pounds of cellulose or 350 pounds of fiberglass per hour and weighs 177 pounds. This system allows for ease of transportation to the job site in addition to timely installation of attic insulation – either cellulose or fiberglass – at 3/4 hour for R-19 in a 1000 square foot attic.

Ease Of Use

Ease of transfer between retail location and jobsite is enabled by its small size & built-in wheels. The system's control panel and wired remote provide for ease of operation from either the unit or the attic. The hopper holds approximately 1/2 bag of cellulose or 1/3 bag of fiberglass. Hose, connectors and clamps come standard -- everything you need to begin using immediately.



Capabilities

The FORCE/1 comes equipped with a slide gate to control material flow -- providing its users sidewall retrofit capabilities in addition to attic installations. Be it cellulose drill & fill or fiberglass dense pack, this system can do-it-all.

Total Reliability

The direct drive transmission delivers years of trouble-free airlock and agitator operation with no maintenance requirements. The urethane seals enhance the durability of this system by lasting 3 to 5 times longer than the industry average -- providing longer durations of peak performance between seal replacement. Wrap it all up in polyethylene construction to resist dents and dings, this little tank (as some in the industry affectionately refer to our FORCE/1) maintains an attractive combination of aesthetics and capabilities over years of use.


As with all Intec systems, the FORCE/1 is technically supported by Intec's customer service team providing for a system experience offering some of the highest industry uptimes and lowest life-cycle costs.

COMES STANDARD WITH



- (2) 50' x 2-1/2" Blowing hose
- (1) 2-1/2" Steel hose connector
- (3) 2-1/2" Stainless steel hose clamps
- (1) 50' 14/3 attached power cord
- (1) 100' Remote cord
- Stainless steel airlock inserts
- 6" wheels
- Pinset material slide gate

PRODUCTION



Cellulose Production
970 lbs per hour



Fiberglass Production
350 lbs per hour

Specifications



Dimensions	18"W x 34"L x 41"H
Weight (machine only)	177 lbs
Weight (shipping)	245 lbs
Production	970 lbs/hr - Cellulose 350 lbs/hr - Fiberglass
Hose Outlet Size	2 1/2"
Remote Cord	16/4 x 100'
Hopper Capacity	4.25 cu. ft.
Drive motor	3/4 HP - 8.4 amps
Transmission	Custom, Direct drive
Airlock	6.5" x 7.25" opening, steel
Blower	2 Stage, 8 amp, 104 cfm @ 3.2 psi
Electrical*	115 VAC / 60 Hz
Power cord	(1) 14/3 x 50'
Warranty	1 year limited; 90 days electric, airlock system and blower

* 230 VAC / 50 Hz available upon request

Electrical Features



- Main control switches
- Agitator circuit breaker
- 50' Power cord (attached)
- 100' Remote cord (attached)

Agitator Options



• For Cellulose materials

• For Fiberglass materials

Accessories



**Steel Hose
Connectors & Reducers**



**Hose Swivels
2-6" Available**



**Contractor
Kit**



Pressure Gauge

Distributed By

The Intec Pledge

*Provide the finest
equipment in the industry
with the highest standards
while continuing to strive
for 100% satisfaction.*

Manufactured By



1-800-666-1611

3771 Monarch Street
Erie, CO 80516 USA

Local: 303-833-6644
Fax: 303-833-6650
www.intecorp.com