

## Cold Water Gasoline Belt Drive

Equipped with a heavy-duty belt drive system, the gas-driven CW Premium Series is deemed the workhorse of the Mi-T-M industrial pressure washer line.

To see more online, scan here  
or go to [www.mitm.com](http://www.mitm.com):



### Pump

- External bypass system allows more water into the system to protect from heat build-up
- Forged brass manifold (Nickel plated brass on 4000-PSI models)
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

### Frame

- Powder coated steel frame and base plate with 1/4-inch tube handles
- Two-piece belt guard with 1/4-turn release
- Flat-free tires

### Unit Includes:

- 50-foot x 3/8-inch non-marking hose with quick connects
- Insulated trigger gun with safety lock-off



CW-3504-5MGS

### Limited Warranties:

**1 Year** Mi-T-M Unloader  
**5 Year** Subaru Engine  
3500 & 4000-PSI models

**3 Year** Honda Engine  
**10 Year** Pump

**3 Year** Vanguard Engine



MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	Mi-T-M NO.	UNLOADER	NOZZLES	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CW-2505-4MGGH	2500	4.4	389cc Honda OHV	General	3-0202	Preset pressure	0°, 15°, 25° & 40°	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-3004-4MGGH	3000	3.5	389cc Honda OHV	General	3-0202	Preset pressure	0°, 15°, 25° & 40°	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-3504-5MGGH	3500	3.8	389cc Honda OHV	General	3-0203	Mi-T-M, preset pressure	0°, 15°, 25° & 40°	48in.	46x28x30in.	290 lb.	216 lb.
CW-3504-5MGS	3500	3.8	404cc Subaru OHC	General	3-0203	Mi-T-M, preset pressure	0°, 15°, 25° & 40°	48in.	46x28x30in.	290 lb.	216 lb.
CW-4004-5MGGH	4000	3.5	389cc Honda OHV	General	3-0075	Mi-T-M, preset pressure	0°, 15°, 25° & 40°	48in.	46x28x30in.	290 lb.	216 lb.
CW-4004-5MV0	4000	4.0	480cc Vanguard OHV, electric start - battery included	General	3-0075	Mi-T-M, preset pressure	0°, 15°, 25° & 40°	48in.	46x28x30in.	330 lb.	256 lb.

### Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0045	Electric start - battery included	3000 to 4000-PSI Honda models
851-0338	50-ft. x 3/8-in. non-marking hose	All models	CX-0054	Roll cage	All Honda models & CW-3504-5MGS
AW-8400-0021	Low pressure detergent injector	All models	CX-0055	Roll cage	CW-4004-5MV0
CX-0005	48-in. insulated dual lance	All models			